

# **ECONOLITE - ENCLOSED TRAILERS**

## **SINGLE AXLE**

### **STANDARD EQUIPMENT**

#### **FRAME**

Rectangle Tubular Steel Construction - Welded All Four Sides  
Main Frame Runner 2 x 3 1/8" Thick Tubing  
Crossmember for 5 & 6 Wide - Z-Member  
Crossmember for 7 Wide - 2 x 2 Tubing, 14 Gage  
Tube Uprights 24" On Center (1"x 1" & 1"x 2" 16 Gauge Tubing)  
Heavy-Duty Single Rear Door 5 Wide (1" x 1" 16 Gauge Steel Tubing with 3/8" Exterior Plywood)  
Heavy-Duty Split Rear Doors for 6 & 7 Wide (1" x 1" 16 Gauge Steel Tubing with 3/8" Exterior Plywood)  
V-Nose Style Front Design For Aero-Dynamic  
Jig Welded Technology - Frame, Walls, Roof, Front & Doors (Complete Trailer)  
Frame is Primed & Painted Black With Oil Base Paint (Electrostatic Process)  
2" Coupler - 8,000 lb Capacity  
2,000 lb. Tongue Jack With Sand Pad/Foot  
27" - 5,000 lb. Safety Chains (Class III)

#### **RUNNING GEAR**

2,990 lb. GVW - One 3,500 lb. Axle (Dexter Axle)  
Leaf Spring Axle, Bolt on Application  
E-Z Lube Wheel Bearings  
15" Bias Ply Trailer Tires ,Load Range "C" (1 Year No Questions Asked Warranty)  
E-Coated White Modular Wheels (Special Priming Process / Rust Prohibitive)

#### **EXTERIOR**

All LED Lighting (Lifetime Warranty), Hermetically Sealed  
All Aluminum Exterior (.024 Gauge Sheet)  
Galvalume Roof - Mill Finish  
All Exterior Hardware is Aluminum or Stainless Steel (Hinges, Hasp, Cam Bars)  
Aluminum Jeep Style Fenders  
12" Aluminum Diamond Plate Stoneguard

#### **INTERIOR**

3/4" Decking Exterior Grade, B/C Finish  
3/8" Sidewalls Exterior Grade, B/C Finish  
Rear Interior LED Dome Light  
Single Rear Door 5 Wide (1" x 1" 16 Gauge Steel Tubing with 3/8" Exterior Plywood)  
Split Rear Doors for 6 & 7 Wide (1" x 1" 16 Gauge Steel Tubing with 3/8" Exterior Plywood)

**Note: above items are subject to change without notice.**

### **COMMON OPTIONAL EQUIPMENT**

Rear Ramp Door With Spring Assist  
Side Door - 30" , 32" , 36" (1" x 1" 16 Gauge Steel Tubing with 3/8" Exterior Plywood)  
Interior Shelves (Welded Steel Tubing To Wall For Strength, Covered With 3/4" Exterior Plywood)  
Roof Vent (1" x 2" 16 Gaged Steel Support Frame)  
Spare Tire Mount - Interior  
Triple Weed Eater Racks - Lockable  
12 Exterior Color Choices  
Aluminum Diamond Plate Stoneguard 24" High  
Recessed Floor Ties With Backing Plate (4,000 lb Cap.)  
Wall Ties (400 lb Cap.)  
Stabilizer Jacks  
Electric Brakes with 7-Way Molded Plug and Breakaway Kit

**Call For Other Options**